



# RF EP-2820-4ZRC CONTROLLER

## RF LED RGB Controller EP-2820-4ZWMC 4 Zones Wall Mounted Controller

- User-friendly interface, easy and simple operation.
- Operation return function.
- Control up to 4 zones.
- Set 4 scenes at each zone.
- Preset 10 changing modes, with pause function.
- Synchronization function of pattern changes ensure consistent change forever.
- Control synchronously after installing software on iphone, ipad, android.
- Enable to dim brightness of each R, G, B, W channel, in order to mix millions of colors.  
Enable to dim brightness of each R, G, B, W channel, in order to mix millions of color

### SPECIFICATIONS

SENDER: (MODEL: EP-2820-4Z-4ZWMC)

Working temperature: 4.5V(3x1.5V (7 AAA battery))  
 Working current: <22mA  
 Dormancy current: <20µA  
 Working frequency: 434MHZ/868MHZ/915MHZ (optional)  
 Transmit power: ≥5dBm

RECEIVER: (EP-1009-EA-CV) - CONSTANT VOLTAGE

Input voltage: 12-36VDC  
 Output voltage: 12-36VDC  
 EP-1009-EA-WI-CV: 4 channels x 5A, 4channels x (60-180W)

RECEIVER: (EP-1009-350-EA-CC) - CONSTANT CURRENT

Input voltage: 12-36VDC  
 Output voltage: 12-36VDC  
 EP-1009-350-EA-WI-CC: 4 channels x 350mA,  
4 channels x (4.2-12.6W)

RECEIVER: (EP-1009-1000-EA-CC) - CONSTANT CURRENT

Input voltage: 12-36VDC  
 Output voltage: 12-36VDC  
 EP-1009-1000-EA-WI-CC: 4 channels x 700mA,  
4 channels x (8.4-25.2W)



# EPIC™ GLOBAL SYSTEM

BEYOND THE LIMITS!