

# SPECIFICATION IL-TG-RGB-5050-30

THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING

## INDOOR RGB

### IL-TG-RGB-5050-30-IP20

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 30LED s/m
- Dimensions: 500mm x 10mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 7.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


## OUTDOOR RGB

### IL-TG-RGB-5050-30-IP68

- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 30LED s/m
- PCB Dimension: 500mm x 10mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 7.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller




## RGB - 5050 - 12V - 30LED/m - 7.2 W/m



V. 320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved

## RGB - 5050 - 24V - 30LED/m - 14.4 W/m



## ORDERING

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-RGB-5050-30</b>	— <input type="text"/>	— <input type="text"/>	— <input type="text"/>
ThinGlow™ RGB-5050 30 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above